

Ref: SSS 04.2.1
SPECIFICATION SELECTION SHEET
MODEL 043-B
RESIDENTIAL SERVICE REGULATOR



Energy Metering

Basic 043-B Models	Description	Code
043-B Straight Body	Straight Body Regulator with Internal Relief Valve	A1
043-B Angle Body	Angle Body Regulator with Internal Relief Valve	A2

Inlet pipe diameter	Outlet pipe diameter	Code
3/4"	3/4"	B1
3/4"	1"	B2
1"	1"	B3
3/8"	3/8"	B4
1/2"	1/2"	B5

Outlet Pressure Range	Spring Color	Code
3½" w.c. to 10½" w.c.	Silver	C1
6" w.c. to 14" w.c.	Green	C2
12.0" w.c. to 28.0" w.c.	Red	C3
6" w.c. to 8" w.c.	Blue	C4
1 p.s.i.g. to 2 p.s.i.g.	Black	C5

Orifice size	Code
1/2"	D1
7/16"	D2
3/8"	D3
5/16"	D4
1/4"	D5
3/16"	D6
1/8"	D7

Taps	Code
None	E1
Inlet	E2
Outlet	E3
Both	E4

Body Coating	Code
None	F1
E-Coating	F2
B633 Yellow Zinc Coating	F3
Clear Zinc Coating	F4

Options	
Inlet pressure	
Outlet pressure (Set Point)	
Body Configuration Number (Position)	

Special Instructions:

Please reference specification bulletin R 1300 for full specification details.
Please circle your choice in each category or include code choices on your purchase order.
Standard Construction and Testing at Manufacturer's Recommended settings will apply unless otherwise specified above. AGA Gray paint finish is supplied unless otherwise specified.

Purchase Order No.	
---------------------------	--