




Gas Cocks



Lever Handle Air Cock

Maximum Working Pressure: 5 psig

Size	Part #	Α	В	С	D
1/8"	11020	1-9/16"	1-3/8"	7/8"	1"






Forged Brass Ball Valves

UL Listed: 1/4" - 2", 500 psig CGA certified: 1/4" - 2", 125 psig AGA certified: 1/4" - 3", 1/2 psig

Size	Part #	Α	В	С	C_{V}
1/4"	10328	1-7/8"	1-7/16"	3"	12
3/8"	10324	1-7/8"	1-7/16"	3"	12
1/2"	10334	2-7/16"	1-1/2"	3"	20
3/4"	10344	2-3/4"	1-7/8"	3-3/4"	42
1"	10348	3-5/16"	2-3/8"	4-3/4"	78
1-1/4"	10354	3-7/8"	2-5/8"	4-3/4"	132
1-1/2"	10357	4-3/4"	3-1/4"	6"	207
2"	10372	5"	3-1/2"	6"	346
2-1/2"	14180	6-1/16"	4-1/2"	7-7/8"	484
3"	14558	7-1/16"	5"	7-7/8"	639
4"	14559	8-7/8"	6"	9-7/8"	1092






Forged Brass Ball Valves with Side Tap

UL Listed: 500 psig CGA certified: 125 psig AGA certified: 1/2 psig


Size	Part #	Α	В	С	D	Cv
1/2"	14969	2-7/16"	1-1/2"	3"	1/8"	20
3/4"	12961	2-3/4"	1-7/8"	3-3/4"	1/8"	42
1"	19122	3-5/16"	2-3/8"	4-3/4"	1/8"	78
1-1/4"	14916	3-7/8"	2-5/8"	4-3/4"	1/4"	132
1-1/2"	14918	4-3/4"	3-1/4"	6"	1/4"	207
2"	14926	5"	3-1/2"	6"	1/4"	346





FM Approved Supervisory Gas Cocks Maximum Working Pressure: 50 psig

Size	Part #	Α	В	С	D	Cv
1/2"	17379	3-3/4"	5-1/4"	2-7/8"	8-1/8"	19
3/4"	15953	3-3/4"	5-1/4"	2-7/8"	8-1/8"	31
1"	15955	4-1/4"	5-5/8"	3-5/16"	9-5/8"	48
1-1/4"	15959	5"	7-1/8"	4"	9-5/8"	92
1-1/2"	15961	5"	7-1/8"	4"	9-5/8"	130
2"	17224	6"	9"	5-1/8"	14-3/4"	220








Lubricated Plug Cocks

UL listed, CGA certified
Maximum Working Pressure: 175 psig
(Wrench Shipped Loose)

Size	Part #	Α	В	С	c_v
1/2"	18812	3-3/4"	5-1/4"	2-7/8"	19
3/4'	18813	3-3/4"	5-1/4"	2-7/8"	31
1"	18814	4-1/4"	5-5/8"	3-5/16"	42
1-1/4"	18815	5"	7-1/8"	4"	72
1-1/2"	18816	5"	7-1/8"	4"	85
2"	18817	6"	9"	5-1/8"	150
2-1/2"	18818	6-3/4"	9-9/16"	5-3/8"	220
3"	18819	7-5/8"	11-7/16"	6-1/2"	345
4"	18820	10"	13-3/4"	7-3/4"	525






Eccentric Plug Cocks

(UL Listed & CSA Approved)

Maximum Working Pressure: 175 psig

Size	Part #	Α	В	С	D	C_V
1/2"	19790	3-1/4"	4-3/4"	3-1/2"	4"	9
3/4"	19791	3-3/4"	5"	3-5/8"	4"	22
1"	19792	4-1/4"	5-11/16"	4"	5"	35
1-1/4"	19793	4-3/4"	6-1/8"	4-1/4"	5"	54
1-1/2"	19794	5"	6-3/8"	4-3/8"	6"	78
2"	19795	5-1/2"	7"	4-3/4"	6"	135
2-1/2"	19796	6-7/8"	8-3/8"	5-1/2"	8"	180
3"	19797	7-1/2"	9"	5-3/4"	10"	270
4"	19798	9-1/4"	11-1/8"	6-7/8"	12"	500






Aluminum Pilot Valves

AGA Approved

Type	Part #	Inlet	Outlet
Right Angle	16494	1/8" m. or f.	1/4" tubina





Brass Hose Cock

1/8" NPT male x 1/8" NPT female Part# 10322 CGA certified: 1/2 psig

Hose Fitting for Hose Cock

1/8" NPT male x 1/4" tube Part# 14380

